

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBS-50

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0	49.2	55.2	62.4	70.8	76.2	81.6	88.2
						QLPM	0	820	920	1040	1180	1270	1360	1470
						H/Stage	22	18.5	17	15.5	14	12.5	11.3	10.2
1	SBS-50	2	7.5	10	100	TOTAL HEAD IN METRE	44	37	34	31	28	25	23	21
2	SBS-50	3	11	15	100		66	56	51	47	42	38	34	31
3	SBS-50	4	15	20	100		88	74	68	62	56	50	45	41
4	SBS-50	5	18.5	25	100		110	93	85	78	70	63	56	51
5	SBS-50	6	22	30	100		132	111	102	93	84	75	67	61
6	SBS-50	7	25	35	100		154	130	119	109	98	88	78	71
7	SBS-50	8	30	40	100		176	148	136	124	112	100	89	81
8	SBS-50	9	34	45	100		198	167	153	140	126	113	100	91
9	SBS-50	10	37	50	100		220	185	170	155	140	125	111	101
10	SBS-50	11	45	60	100		242	204	187	171	154	138	112	111
11	SBS-50	12	45	60	100		264	222	204	186	168	150	133	121

