

# U-Neel®

## SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL**

Model - SBS-60

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM <sup>3</sup> /HR	0	64.8	69	72	81	88.8	93	99
						QLPM	0	1080	1150	1200	1350	1480	1550	1650
						H/Stage	22.5	18.5	17	15.5	14	12.5	11	10
1	SBS-60	2	9.3	12.5	100	TOTAL HEAD IN METRE	45	37	34	31	28	25	22	20
2	SBS-60	3	15	20	100		68	56	51	46	42	37	33	30
3	SBS-60	4	18.5	25	100		90	74	68	62	56	50	44	40
4	SBS-60	5	22	30	100		113	93	85	77	70	62	55	50
5	SBS-60	6	25	35	100		135	111	102	93	84	75	66	60
6	SBS-60	7	34	45	100		158	130	119	108	98	87	77	70
7	SBS-60	8	37	50	100		180	148	136	123	112	100	88	80
8	SBS-60	10	45	60	100		225	185	170	155	140	125	110	100
9	SBS-60	11	45	60	100		248	204	187	170	154	137	121	110
10	SBS-60	12	55	70	100		270	222	204	186	168	150	132	120

