

SUPER MODEL

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA BORE WELL (V6/V8)

Model SBS-40

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	QM ³ /HR	0	45	48	51	57	63	70.5	76.5
						QLPM	0	750	800	850	950	1050	1175	1275
						H/Stage	19	16.5	15	14.5	13.5	11.5	10	8.5
1	SBS-40	2	7.5	5.5	75/100	TOTAL HEAD IN METRE	38	33	30	29	27	23	20	17
2	SBS-40	3	12.5	9.3	75/100		57	50	45	44	41	35	30	26
3	SBS-40	4	15	11	75/100		76	66	60	58	54	46	40	34
4	SBS-40	5	20	15	75/100		95	83	75	73	68	58	50	43
5	SBS-40	6	25	18.5	75/100		114	99	90	87	81	69	60	51
6	SBS-40	7	30	22	75/100		133	116	105	102	95	81	70	60

