

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - M-130

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	66	84	96	121.5	133.5	145.5	156	168
							QLPM	0	1100	1400	1600	2025	2225	2425	2600	2800
							H/Stage	31.0	26.3	25.0	24.0	22.3	21.0	19.0	17.0	14.3
1	M-130	2	25	18.5	125	-	TOTAL HEAD IN METRE	62	53	50	48	45	42	38	34	29
2	M-130	3	40	30	125	-		93	80	75	72	68	63	57	51	43
3	M-130	4	50	37	125	-		124	106	100	96	90	84	76	68	58
4	M-130	5	62	46.5	125	-		155	132	125	120	112	105	95	85	72
5	M-130	6	72	53.5	125	-		186	158	150	144	134	126	114	102	86
6	M-130	7	82	61	125	-		217	184	175	168	156	147	133	119	100
7	M-130	8	100	75	125	-		248	211	200	192	179	168	152	136	115
8	M-130	9	125	93	125	-		279	237	225	216	201	189	171	153	129
9	M-130	10	135	100	125	-		310	263	250	240	223	210	190	170	143

