

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - M-200

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	QM ³ /HR	0	78	108	150	168	183	210	219	228
						QLPM	0	1300	1800	2500	2800	3050	3500	3650	3800
						H/Stage	33.6	30.0	28.0	25.0	23.0	21.0	17.0	15.0	12.0
1	M-200	1	15	20	125/150	TOTAL HEAD IN METRE	34	30	28	25	23	21	17	15	12
2	M-200	2	30	40	125/150		67	60	56	50	46	42	34	30	24
3	M-200	3	45	60	125/150		101	90	84	75	69	63	51	45	36
4	M-200	4	60	80	125/150		134	120	112	100	92	84	68	60	48
5	M-200	5	75	100	125/150		168	150	140	125	115	105	85	75	60
6	M-200	6	90	120	125/150		201	180	168	150	138	126	102	90	72
7	M-200	7	110	150	125/150		235	210	196	175	161	147	119	105	84

