

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - M-225

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	QM ³ /HR	0	96	126	162	180	195	219	228	234
						QLPM	0	1600	2100	2700	3000	3250	3650	3800	3900
						H/Stage	35.0	30.0	28.0	25.0	23.0	21.0	17.0	15.0	12.0
1	M-225	1	17	22.5	125/150	TOTAL HEAD IN METRE	35	30	28	25	23	21	17	15	12
2	M-225	2	34	45	125/150		70	60	56	50	46	42	34	30	24
3	M-225	3	52	70	125/150		105	90	84	75	69	63	51	45	36
4	M-225	4	66	90	125/150		140	120	112	100	92	84	68	60	48
5	M-225	5	82	110	125/150		175	150	140	125	115	105	85	75	60
6	M-225	6	101	135	125/150		210	180	168	150	138	126	102	90	72

