

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - M-250

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	QM ³ /HR	0	66	81	120	150	186	198	210	216
						QLPM	0	1100	1350	2000	2500	3100	3300	3500	3600
						H/Stage	40.0	36.0	34.0	32.0	30.0	27.0	25.0	22.0	15.0
1	M-250	1	18.5	25	125/150	TOTAL HEAD IN METRE	40	36	34	32	30	27	25	22	15
2	M-250	2	37	50	125/150		80	72	68	64	60	54	50	44	30
3	M-250	3	55	75	125/150		120	108	102	96	90	81	75	66	45
4	M-250	4	75	100	125/150		160	144	136	128	120	108	100	88	60
5	M-250	5	93	125	125/150		200	180	170	160	150	135	125	110	75
6	M-250	6	110	150	125/150		240	216	204	192	180	162	150	132	90

