

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - SB-60

Mixed Flow

Max. Out Side Dia. 243 mm

| Sr. No. | Pump Type | Stage | KW | H.P. | Out let Size mm | ISI Mark | QM ³ /HR | 0 | 36 | 48 | 69 | 84 | 96 | 102 |
|---------|-----------|-------|----|------|-----------------|----------|------------------------|------|------|------|------|------|------|------|
| | | | | | | | QLPM | 0 | 600 | 800 | 1150 | 1400 | 1600 | 1700 |
| | | | | | | | H/Stage | 23.8 | 20.5 | 19.3 | 16.4 | 14.1 | 12.0 | 10.9 |
| 1 | SB-60 | 7 | 30 | 42 | 100 | - | TOTAL HEAD IN METRE | 165 | 145 | 136 | 116 | 97 | 80 | 71 |
| 2 | SB-60 | 8 | 37 | 52 | 100 | - | | 190 | 164 | 154 | 131 | 113 | 96 | 87 |
| 3 | SB-60 | 9 | 37 | 52 | 100 | ISI | | 213 | 185 | 173 | 147 | 127 | 108 | 98 |
| 4 | SB-60 | 10 | 45 | 62 | 100 | ISI | | 238 | 205 | 193 | 164 | 141 | 120 | 109 |
| 5 | SB-60 | 11 | 55 | 72 | 100 | - | | 262 | 226 | 212 | 180 | 155 | 132 | 120 |
| 6 | SB-60 | 12 | 55 | 72 | 100 | - | | 286 | 246 | 231 | 196 | 169 | 144 | 131 |
| 7 | SB-60 | 13 | 63 | 85 | 100 | - | | 310 | 267 | 251 | 213 | 184 | 156 | 142 |
| 8 | SB-60 | 14 | 63 | 85 | 100 | - | | 334 | 288 | 271 | 230 | 198 | 168 | 153 |

