

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model SB-60		Mixed Flow					Max. Out Side Dia. 243 mm								
Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	39	51	69	87.6	97.8	103	128
							QLPM	0	650	850	1150	1460	1630	1715	2130
							H/Stage	23.0	20.0	18.5	17.0	14.0	12.0	11.0	1.0
1	SB-60	7	40	30	100	-	TOTAL HEAD IN METRE	161	140	130	119	98	84	77	7
2	SB-60	8	50	37	100	-		184	160	148	136	112	96	88	8
3	SB-60	9	50	37	100	ISI		207	180	167	153	126	108	99	9
4	SB-60	10	62	46.5	100	ISI		230	200	185	170	140	120	110	10
5	SB-60	11	72	53.5	100	-		253	220	204	187	154	132	121	11
6	SB-60	12	72	53.5	100	-		276	240	222	204	168	144	132	12
7	SB-60	13	82	61	100	-		299	260	241	221	182	156	143	13
8	SB-60	14	82	61	100	-		322	280	259	238	196	168	154	14

