

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

**SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL**

Model - SB-60

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM <sup>3</sup> /HR	0	36	48	69	84	96	102
							QLPM	0	600	800	1150	1400	1600	1700
							H/Stage	23.8	20.5	19.3	16.4	14.1	12.0	10.9
1	SB-60	7	30	42	100	-	TOTAL HEAD IN METRE	165	145	136	116	97	80	71
2	SB-60	8	37	52	100	-		190	164	154	131	113	96	87
3	SB-60	9	37	52	100	ISI		213	185	173	147	127	108	98
4	SB-60	10	45	62	100	ISI		238	205	193	164	141	120	109
5	SB-60	11	55	72	100	-		262	226	212	180	155	132	120
6	SB-60	12	55	72	100	-		286	246	231	196	169	144	131
7	SB-60	13	63	85	100	-		310	267	251	213	184	156	142
8	SB-60	14	63	85	100	-		334	288	271	230	198	168	153

