

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - SB-70

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM ³ /HR	0	48	60	72	78	90	96	108
							QLPM	0	800	1000	1200	1300	1500	1600	1800
							H/Stage	24.2	20.4	19.0	17.2	16.6	14.2	13.2	8.2
1	SB-70	6	30	42	100	-	TOTAL HEAD IN METRE	142	122	114	103	100	85	79	49
2	SB-70	7	37	52	100	-		166	139	130	120	115	100	90	68
3	SB-70	9	45	62	100	ISI		213	183	171	155	150	128	119	74
4	SB-70	10	55	72	100	ISI		242	204	190	172	166	142	132	82
5	SB-70	11	60	82	100	-		266	224	209	189	183	156	145	90
6	SB-70	12	63	85	100	-		290	244	228	206	199	170	158	98
7	SB-70	13	75	100	100	-		315	265	247	223	216	185	172	106
8	SB-70	14	75	100	100	-		340	286	266	241	233	200	186	115

