

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - SB-80

Mixed Flow

Max. Out Side Dia. 243 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Out let Size mm	ISI Mark	QM ³ /HR	0	60	72	90	108	120	126	132
							QLPM	0	1000	1200	1500	1800	2000	2100	2200
							H/Stage	23.8	20.0	19.0	17.2	14.4	11.8	10.6	8.8
1	SB-80	5	30	42	100	-	TOTAL HEAD IN METRE	119	100	96	87	73	60	53	44
2	SB-80	6	37	52	100	-		141	119	114	102	86	76	67	53
3	SB-80	8	45	62	100	ISI		193	160	152	140	118	98	86	70
4	SB-80	9	55	72	100	ISI		215	179	171	151	127	112	95	79
5	SB-80	10	63	85	100	ISI		238	200	190	172	144	118	106	88
6	SB-80	11	63	85	100	-		262	220	209	189	158	130	117	97
7	SB-80	12	75	100	100	-		286	240	228	206	172	142	128	106

