

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 250 mm (10") OR ABOVE DIA. BOREWELL

Model - SB-80							Mixed Flow		Max. Out Side Dia. 243 mm						
Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	45.6	70.5	101	114	120	138	
							QLPM	0	760	1175	1675	1900	2000	2300	
							H/Stage	23.3	20.0	18.0	14.7	12.3	11.0	3.3	
1	SB-80	5	40	30	100	-	TOTAL HEAD IN METRE	117	100	90	73	62	55	17	
2	SB-80	6	50	37	100	-		140	120	108	88	74	66	20	
3	SB-80	8	62	46.5	100	ISI		187	160	144	117	99	88	27	
4	SB-80	9	72	53.5	100	ISI		210	180	162	132	111	99	30	
5	SB-80	10	82	61	100	ISI		233	200	180	147	123	110	33	
6	SB-80	11	82	61	100	-		257	220	198	161	136	121	37	
7	SB-80	12	100	75	100	-		280	240	216	176	148	132	40	

