

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 80 mm (3") OR ABOVE DIA. BOREWELL

Max. Out Side Dia. 74 mm

Model - UG310

RADIAL FLOW

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	3.3	3.6	3.9	4.2	4.5	4.8	5.1	5.4	5.7
						QLPM	55	60	65	70	75	80	85	90	95
						H/Stage	2.5	2.3333	2.1667	2	1.8333	1.667	1.3333	1	0.667
1	UG310	6	0.37	0.5	32	TOTAL HEAD IN METRES	15	14	13	12	11	10	8	6	4
2	UG310	9	0.56	0.75	32		24	22	20	18	16	14	12	9	6
3	UG310	12	0.75	1	32		32	30	27	24	21	18	15	12	8
4	UG310	15	0.93	1.25	32		39	36	33	30	27	23	19	15	10
5	UG310	18	1.12	1.5	32		46	43	40	36	32	28	23	18	12

