

U-Neel®

SUBMERSIBLE PUMPS

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR **80 mm (3")** OR ABOVE DIA. BOREWELL

Model - UG32

RADIAL FLOW

Max. Out Side Dia. 74 mm

Sr. No.	Pump Type	Stage	KW	H.P.	Outlet Size mm	QM ³ /HR	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7	3	
						QLPM	10	15	20	25	30	35	40	45	50	
						H/Stage	4	3.8	3.5	3.2	2.8	2.4	2	1.4	0.9	
1	UG32	10	0.37	0.5	25	TOTAL HEAD IN METRES	40	38	35	32	28	24	20	14	9	
							60	56	52	47	41	36	29	21	14	
							80	75	70	63	55	48	39	28	18	
							104	98	91	83	72	62	50	36	23	
							120	116	109	98	86	74	61	43	28	
2	UG32	15	0.56	0.75	25											
3	UG32	20	0.75	1	25											
4	UG32	26	0.93	1.25	25											
5	UG32	30	1.12	1.5	25											

