



FOR SPECIFIC MODELS ONLY

PRICE LIST / PERFORMANCE TABLE OF ENERGY EFFICIENT (STAR RATING) SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - Type 5K-40

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	HP	KW	Outlet Size mm	ISI Mark	STAR RATING	TOTAL HEAD IN METRES							
							QM ³ /HR	0	7.8	8.7	9	9.6	12.9	15.6
							QLPM	0	130	145	150	160	215	260
							H/Stage	9.5	8.5	7.7	7	6.7	5.25	3
1	5K-40/7	3	2.2	50	ISI	-		67	60	54	49	47	36.5	21
2	5K-40/8	3	2.2	50	ISI	-		76	68	62	56	54	42	24
3	5K-40/9	4	3	50	ISI	-		86	77	69.5	63	60	47	27
4	5K-40/10	4	3	50	ISI	-		95	85	77	70	67	52.5	30
5	5K-40/11	4	3	50	ISI	-		104	93	85	77	74	57.5	33
6	5K-40/12	5	3.7	50	ISI	-		114	102	92.5	84	81	63	36
7	5K-40/13	5	3.7	50	ISI	-		123	111	100.5	91	87	68	39
8	5K-40/14	6	4.5	50	ISI	-		133	119	108	98	94	73.5	42
9	5K-40/15	6	4.5	50	ISI	-		143	128	115.5	105	101	78.5	45
10	5K-40/16	6	4.5	50	ISI	-		152	136	123.5	112	107	84	48
11	5K-40/17	7.5	5.5	50	ISI	-		162	145	131	119	114	89	51
12	5K-40/18	7.5	5.5	50	ISI	-		171	153	139	126	121	94.5	54
13	5K-40/19	7.5	5.5	50	ISI	-		181	162	146.5	133	127	99.5	57
14	5K-40/20	7.5	5.5	50	ISI	-		190	170	154	140	134	105	60
15	5K-40/21	7.5	5.5	50	ISI			200	178	162	147	141	110	63
16	5K-40/22	10	7.5	50	ISI	-		209	187	169.5	154	148	115.5	66
17	5K-40/23	10	7.5	50	ISI	-		219	196	177.5	161	154	120.5	69
18	5K-40/24	10	7.5	50	ISI	-		228	204	185	168	161	126	72
19	5K-40/25	10	7.5	50	ISI	-		238	213	192.5	175	168	131	75
20	5K-40/26	10	7.5	50	ISI	-		247	221	200.5	182	174	136.5	78
21	5K-40/27	10	7.5	50	ISI	-		257	230	208	189	181	141.5	81
22	5K-40/28	12.5	9.3	50	ISI	-		266	238	216	196	188	147	84
23	5K-40/29	12.5	9.3	50	ISI	-		276	247	223.5	203	195	152	87
24	5K-40/30	12.5	9.3	50	ISI	-		285	255	231	210	201	157.5	90



Cost Per Stage : 880.00