



FOR SPECIFIC MODELS ONLY

PRICE LIST / PERFORMANCE TABLE OF ENERGY EFFICIENT (STAR RATING) SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model - Type 5K-60

RADIAL FLOW

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type & Stage	HP	KW	Outlet Size mm	ISI Mark	STAR RATING	QM ³ /HR	0	11.4	12.3	12.6	13.5	17.1	21.6
							QLPM	0	190	205	210	225	285	360
							H/Stage	11.0	9.5	8.8	8.0	7.7	6.0	3.0
1	5K-60/7	4	3	50	ISI	-	77	67	62	56	54	42	21	
2	5K-60/8	5	3.7	50	ISI	-	88	76	70.5	64	62	48	24	
3	5K-60/9	5	3.7	50	ISI	-	99	85	79.5	72	69	54	27	
4	5K-60/10	6	4.5	50	ISI	-	110	95	88	80	77	60	30	
5	5K-60/11	6	4.5	50	ISI	-	121	104	97	88	85	66	33	
6	5K-60/12	7.5	5.5	50	ISI	-	132	114	106	96	93	72	36	
7	5K-60/13	7.5	5.5	50	ISI	-	143	124	114.5	104	100	78	39	
8	5K-60/14	7.5	5.5	50	ISI	-	154	133	123.5	112	108	84	42	
9	5K-60/15	10	7.5	50	ISI	-	165	143	132	120	116	90	45	
10	5K-60/16	10	7.5	50	ISI	-	176	152	141	128	123	96	48	
11	5K-60/17	10	7.5	50	ISI	-	187	162	150	136	131	102	51	
12	5K-60/18	10	7.5	50	ISI	-	198	171	158.5	144	139	108	54	
13	5K-60/19	12.5	9.3	50	ISI	-	209	181	167.5	152	146	114	57	
14	5K-60/20	12.5	9.3	50	ISI	-	220	190	176	160	154	120	60	
15	5K-60/21	12.5	9.3	50	ISI	-	231	200	185	168	162	126	63	
16	5K-60/22	12.5	9.3	50	ISI	-	242	209	194	176	170	132	66	
17	5K-60/23	15	11	50	ISI	-	253	219	202.5	184	177	138	69	
18	5K-60/24	15	11	50	ISI	-	264	228	211.5	192	185	144	72	
19	5K-60/25	15	11	50	ISI	-	275	238	220	200	193	150	75	
20	5K-60/26	17.5	13	50	ISI	-	286	247	229	208	200	156	78	
21	5K-60/27	17.5	13	50	ISI	-	297	257	238	216	208	162	81	
22	5K-60/28	17.5	13	50	ISI	-	308	266	246.5	224	216	168	84	
23	5K-60/29	17.5	13	50	ISI	-	319	276	255.5	232	223	174	87	
24	5K-60/30	20	15	50	ISI	-	330	285	264	240	231	180	90	
25	5K-60/31	20	15	50	ISI	-	341	295	273	248	239	186	93	
26	5K-60/32	20	15	50	ISI	-	352	304	282	256	247	192	96	

TOTAL HEAD IN METRES

Cost Per Stage : 880.00

