

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model SSK-100

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet size mm	QM ³ /HR	12	12.6	13.8	15.6	18.6	20.4	21.6	24	26.4
						QLPM	200	210	230	260	310	340	360	400	440
						H/Stage	15	14	13	12	10	8	6	4	2
1	SSK-100	3	3	2.2	50	TOTAL HEAD IN METRE	45	42	39	36	30	24	18	12	6
2	SSK-100	4	4	3	50		60	56	52	48	40	32	24	16	8
3	SSK-100	5	5	3.7	50		75	70	65	60	50	40	30	20	10
4	SSK-100	6	6	4.5	50		90	84	78	72	60	48	36	24	12
5	SSK-100	8	7.5	5.5	50		120	112	104	96	80	64	48	32	16
6	SSK-100	10	10	7.5	50		150	140	130	120	100	80	60	40	20
7	SSK-100	12	12.5	9.3	50		180	168	156	144	120	96	72	48	24
8	SSK-100	15	15	11	50		225	210	195	180	150	120	90	60	30
9	SSK-100	18	17.5	13	50		270	252	234	216	180	144	108	72	36
10	SSK-100	20	20	15	50		300	280	260	240	200	160	120	80	40

