

### HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

**Model SSK-125**

**Radial Flow**

**Max. Out Side Dia. 142 mm**

Sr. No.	Pump Type	Stage	HP	KW	Outlet size mm	QM <sup>3</sup> /HR	12.9	16.2	18.6	20.4	22.2	24.6	27.6	30	33
						QLPM	215	270	310	340	370	410	460	500	550
						H/Stage	15	14	13	12	10	8	6	4	2
1	SSK-125	3	4	3	50	TOTAL HEAD IN METRE	45	42	39	36	30	24	18	12	6
2	SSK-125	4	5	3.7	50		60	56	52	48	40	32	24	16	8
3	SSK-125	5	6	4.5	50		75	70	65	60	50	40	30	20	10
4	SSK-125	6	7.5	5.5	50		90	84	78	72	60	48	36	24	12
5	SSK-125	8	10	7.5	50		120	112	104	96	80	64	48	32	16
6	SSK-125	10	12.5	9.3	50		150	140	130	120	100	80	60	40	20
7	SSK-125	12	15	11	50		180	168	156	144	120	96	72	48	24
8	SSK-125	14	17.5	13	50		210	196	182	168	140	112	84	56	28
9	SSK-125	16	20	15	50		240	224	208	192	160	128	96	64	32
10	SSK-125	18	22.5	17	50		270	252	234	216	180	144	108	72	36
11	SSK-125	20	25	18.5	50		300	280	260	240	200	160	120	80	40
12	SSK-125	24	30	22	50		360	336	312	288	240	192	144	96	48

