

HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model SSK-200

Radial Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet size mm	QM ³ /HR	19.5	25.5	27.6	30	36	43.5	46.5	51	54
						QLPM	325	425	460	500	600	725	775	850	900
						H/Stage	15	14	13	11	10	8	6	4	2
1	SSK-200	2	4	3	50	TOTAL HEAD IN METRE	30	28	26	22	20	16	12	8	4
2	SSK-200	3	6	4.5	50		45	42	39	33	30	24	18	12	6
3	SSK-200	4	7.5	5.5	50		60	56	52	44	40	32	24	16	8
4	SSK-200	5	10	7.5	50		75	70	65	55	50	40	30	20	10
5	SSK-200	6	12.5	9.3	50		90	84	78	66	60	48	36	24	12
6	SSK-200	8	15	11	50		120	112	104	88	80	64	48	32	16
7	SSK-200	9	17.5	13	50		135	126	117	99	90	72	54	36	18
8	SSK-200	10	20	15	50		150	140	130	110	100	80	60	40	20
9	SSK-200	12	25	18.5	50		180	168	156	132	120	96	72	48	24
10	SSK-200	15	30	22	50		225	210	195	165	150	120	90	60	30

