

### HIGH HEAD (50 FEET / PER STAGE) (S.S. PUMP)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

**Model SSK-80**

**Radial Flow**

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet size mm	QM <sup>3</sup> /HR	7.20	9	10.8	11.40	13.2	15	16.8	18	20.1
						QLPM	120	150	180	190	220	250	280	300	335
						H/Stage	15	14	13	12	10	8	6	4	2
1	SSK-80	4	3	2.2	50	TOTAL HEAD IN METRE	60	56	52	48	40	32	24	16	8
2	SSK-80	5	4	3	50		75	70	65	60	50	40	30	20	10
3	SSK-80	6	5	3.7	50		90	84	78	72	60	48	36	24	12
4	SSK-80	8	6	4.5	50		120	112	104	96	80	64	48	32	16
5	SSK-80	10	7.5	5.5	50		150	140	130	120	100	80	60	40	20
6	SSK-80	12	10	7.5	50		180	168	156	144	120	96	72	48	24
7	SSK-80	15	12.5	9.3	50		225	210	195	180	150	120	90	60	30
8	SSK-80	18	15	11	50		270	252	234	216	180	144	108	72	36
9	SSK-80	21	17.5	13	50		315	294	273	252	210	168	126	84	42
10	SSK-80	24	20	15	50		360	336	312	288	240	192	144	96	48

