

### SUPER MODEL

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL



#### Model M-12

#### Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	ISI Mark	QM <sup>3</sup> /HR	0	15	18	21	24	27	30	36
							QLPM	0	250	300	350	400	450	500	600
							H/Stage	12.6	10	9.4	8.6	7.8	7.8	6.3	4.1
1	M-12	3	4	3	65	-	TOTAL HEAD IN METRE	38	31	29	26	25	22	20	13
2	M-12	4	5	3.7	65	ISI		51	41	39	35	33	30	27	17
3	M-12	5	6	4.5	65	ISI		63	51	48	44	40	36	33	22
4	M-12	6	7.5	5.5	65	ISI		76	61	58	52	48	43	40	26
5	M-12	8	10	7.5	65	ISI		101	79	76	68	63	57	52	34
6	M-12	9	10	7.5	65	-		113	88	85	77	71	64	57	37
7	M-12	10	12.5	9.3	65	ISI		126	100	94	86	78	70	63	41
8	M-12	12	15	11	65	ISI		150	120	112	102	92	83	73	48
9	M-12	16	20	15	65	-		198	158	146	133	119	105	90	60

