

SUITABLE FOR 150 mm (6") OR ABOVE DIA. BOREWELL

Model SB-12

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm		QM ³ /HR	0	25.5	28.5	31.5	34.5	37.5	43.5
							QLPM	0	425	475	525	575	625	725
							H/Stage	14	10	9	8	7	6	3.5
1	SB-12	3	4	3	65	-	TOTAL HEAD IN METRE	42	30	27	24	21	18	11
2	SB-12	4	5	3.7	65	ISI		56	39	36	32	28	24	14
3	SB-12	5	6	4.5	65	ISI		70	49	45	40	35	30	17
4	SB-12	6	7.5	5.5	65	ISI		84	59	54	48	42	36	21
5	SB-12	7	7.5	5.5	65	-		98	69	63	56	49	42	24
6	SB-12	8	10	7.5	65	ISI		112	79	72	64	56	48	28
7	SB-12	9	10	7.5	65	-		126	89	81	72	63	54	32
8	SB-12	10	12.5	9.3	65	ISI		140	98	90	80	70	60	35
9	SB-12	11	12.5	9.3	65	-		154	108	99	88	77	66	38
10	SB-12	12	15	11	65	ISI		168	118	108	96	84	72	42
11	SB-12	13	15	11	65	-		182	128	117	104	91	78	45
12	SB-12	14	17.5	13	65	-		196	138	126	112	98	84	49
13	SB-12	15	17.5	13	65	-		210	148	135	120	105	90	53
14	SB-12	16	20	15	65	-		224	157	144	128	112	96	56
15	SB-12	17	20	15	65	-		238	167	153	136	119	102	59
16	SB-12	18	22.5	17	65	-		252	177	162	144	126	108	63
17	SB-12	20	25	18.5	65	-		280	197	180	160	140	120	70
18	SB-12	24	30	22	65	-		336	236	216	192	168	144	84

Cost Per Stage : 1530.00

