

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR **150 mm (6")** OR ABOVE DIA. BOREWELL

Model SB-25

Mixed Flow

Max. Out Side Dia. 142 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	ISI Mark	QM ³ /HR	0	31.5	42	46.5	52.5	55.5	63
							QLPM	0	525	700	775	875	925	1050
							H/Stage	16.5	13	11	9.6	8.4	7.4	5.3
1	SB-25	3	7.5	5.5	75	-	TOTAL HEAD IN METRE	50	39	33	29	25	22	16
2	SB-25	4	10	7.5	75	ISI		66	52	44	39	34	30	21
3	SB-25	5	12.5	9.3	75	ISI		83	65	55	48	42	37	26
4	SB-25	6	15	11	75	ISI		99	78	66	58	50	44	32
5	SB-25	7	17.5	13	75	-		116	91	77	67	59	52	37
6	SB-25	8	20	15	75	ISI		132	104	88	77	67	59	42
7	SB-25	9	22.5	17	75	-		149	117	99	87	75	66	47
8	SB-25	10	25	18.5	75	-		165	130	110	96	84	74	53
9	SB-25	11	30	22	75	-		182	143	121	106	92	81	58
10	SB-25	12	30	22	75	-		198	156	132	116	101	89	63

