

SUPER MODEL

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 175 mm (7") OR ABOVE DIA BORE WELL (V6/V7)

Model SB-25						Mixed Flow						Max. Out Side Dia. 175 mm					
Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	QM ³ /HR	0	42	52.5	58.5	64.5	69	73.5	75	99		
						QLPM	0	700	875	975	1075	1150	1225	1250	1650		
						H/Stage	14.83	10.67	9.67	9.00	8.33	7.67	7.00	6.67	1.67		
1	SB-25	2	5	3.7	75/100	TOTAL HEAD IN METRE	30	21	19	18	17	15	14	13	3		
2	SB-25	3	7.5	5.5	75/100		45	32	29	27	25	23	21	20	5		
3	SB-25	4	10	7.5	75/100		59	43	39	36	33	31	28	27	7		
4	SB-25	5	12.5	9.3	75/100		74	53	48	45	42	38	35	33	8		
5	SB-25	6	15	11	75/100		89	64	58	54	50	46	42	40	10		
6	SB-25	7	17.5	13	75/100		104	75	68	63	58	54	49	47	12		

