

SUPER MODEL

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 175 mm (7") OR ABOVE DIA BORE WELL (V6/V7)

Model SB-60

Mixed Flow

Max. Out Side Dia. 175 mm

| Sr. No. | Pump Type | Stage | HP | KW | Outlet Size mm | QM ³ /HR | 0 | 49.5 | 75 | 84 | 90 | 96 | 102 | 108 |
|---------|-----------|-------|------|------|----------------|---------------------|------|------|------|------|------|------|------|------|
| | | | | | | QLPM | 0 | 825 | 1250 | 1400 | 1500 | 1600 | 1700 | 1800 |
| | | | | | | H/Stage | 20.5 | 17 | 15 | 14 | 13 | 12 | 11 | 10 |
| 1 | SB-60 | 2 | 12.5 | 9.3 | 100 | TOTAL HEAD IN METRE | 41 | 34 | 30 | 28 | 26 | 24 | 22 | 20 |
| 2 | SB-60 | 3 | 17.5 | 13 | 100 | | 62 | 51 | 45 | 42 | 39 | 36 | 33 | 30 |
| 3 | SB-60 | 4 | 25 | 18.5 | 100 | | 82 | 68 | 60 | 56 | 52 | 48 | 44 | 40 |
| 4 | SB-60 | 5 | 30 | 22 | 100 | | 103 | 85 | 75 | 70 | 65 | 60 | 55 | 50 |

Cost Per Stage : 2500.00

