

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-30							Mixed Flow	Max. Out Side Dia. 193 mm									
Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	ISI Mark	QM ³ /HR	0	22.5	30	37.5	43.5	49.5	52.5	57	63	
							QLPM	0	375	500	625	725	825	875	950	1050	
							H/Stage	19.3	16.9	16.1	15.2	14.4	13.7	12.3	11.3	10.4	
1	SB-30	3	10	7.5	75	ISI	TOTAL HEAD IN METRE	58	51	48	46	43	41	37	34	31	
2	SB-30	4	12.5	9.3	75	ISI		77	68	65	61	58	55	49	45	42	
3	SB-30	5	15	11	75	ISI		97	85	81	76	72	68	62	56	52	
4	SB-30	6	20	15	75	ISI		116	102	97	91	86	82	74	68	62	
5	SB-30	7	20	15	75	ISI		135	119	113	106	101	96	86	79	73	
6	SB-30	8	25	18.5	75	ISI		155	135	129	122	115	109	99	90	83	
7	SB-30	9	27	20	75	ISI		174	152	145	137	130	123	111	101	94	
8	SB-30	10	30	22	75	ISI		193	169	161	152	144	137	123	113	104	
9	SB-30	11	35	26	75	ISI		213	186	177	167	158	150	136	124	114	
10	SB-30	12	35	26	75	ISI		232	203	194	182	173	164	148	135	125	
11	SB-30	13	40	30	75	ISI		251	220	210	198	187	178	160	146	135	
12	SB-30	14	45	33.5	75	ISI		271	237	226	213	202	191	173	158	146	
13	SB-30	15	45	33.5	75	ISI		290	254	242	228	216	205	185	169	156	

