

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-40

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	ISI Mark	QM ³ /HR	0	13.2	27.6	42	48.6	57	62.4	69	76.5	84
							QLPM	0	220	460	700	810	950	1040	1150	1275	1400
							H/Stage	22.1	20.4	18.8	17.0	15.8	14.0	12.6	10.8	8.5	6.3
1	SB-40	3	12.5	9.3	75	ISI	TOTAL HEAD IN METRE	66	61	56	51	47	42	38	32	26	19
2	SB-40	4	15	11	75	ISI		88	82	75	68	63	56	50	43	34	25
3	SB-40	5	20	15	75	ISI		111	102	94	85	79	70	63	54	43	32
4	SB-40	6	25	18.5	75	ISI		133	122	113	102	95	84	76	65	51	38
5	SB-40	7	27	20	75	ISI		155	143	132	119	111	98	88	76	60	44
6	SB-40	8	30	22	75	ISI		177	163	150	136	126	112	101	86	68	50
7	SB-40	9	35	26	75	ISI		199	184	169	153	142	126	113	97	77	57
8	SB-40	10	40	30	75	ISI		221	204	188	170	158	140	126	108	85	63
9	SB-40	11	45	33.5	75	ISI		243	224	207	187	174	154	139	119	94	69
10	SB-40	12	50	37	75	ISI		265	245	226	204	190	168	151	130	102	76
11	SB-40	13	50	37	75	ISI		287	265	244	221	205	182	164	140	111	82
12	SB-40	14	62	46.5	75	ISI		309	286	263	238	221	196	176	151	119	88
13	SB-40	15	62	46.5	75	ISI		332	306	282	255	237	210	189	162	128	95

