

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SB-90

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	60	84	96	105	114	126	138
							QLPM	0	1000	1400	1600	1750	1900	2100	2300
							H/Stage	25	22	21	20	19	17	14.8	12
1	SB-90	1	10	7.5	125	-	TOTAL HEAD IN METRE	28	23	20	19	18	15	13	3
2	SB-90	2	20	15	125	ISI		55	45	40	38	35	30	25	5
3	SB-90	3	30	22	125	ISI		83	68	60	56	53	45	38	8
4	SB-90	4	40	30	125	ISI		110	90	80	75	70	60	50	10
5	SB-90	5	45	33.5	125	ISI		138	113	100	94	88	75	63	13
6	SB-90	6	50	37	125	-		165	135	120	113	105	90	75	15
7	SB-90	7	62	46.5	125	-		193	158	140	131	123	105	88	18
8	SB-90	8	72	53.5	125	-		220	180	160	150	140	120	100	20
9	SB-90	9	82	61	125	-		248	203	180	169	158	135	113	23

