

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBR-20

Radial Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	QM ³ /HR	0	10.2	15	18	21	24	27	30	45	
						QLPM	0	170	250	300	350	400	450	500	750	
						H/Stage	19.6	19	18	17	16	15	14	13	1	
1	SBR-20	5	10	7.5	75	TOTAL HEAD IN METRE	98	95	90	85	80	75	70	65	5	
2	SBR-20	6	12.5	9.3	75		117.6	114	108	102	96	90	84	78	7	6
3	SBR-20	7	15	11	75		137.2	133	126	119	112	105	98	91	7	7
4	SBR-20	8	15	11	75		156.8	152	144	136	128	120	112	104	8	8
5	SBR-20	9	20	15	75		176.4	171	162	153	144	135	126	117	9	9
6	SBR-20	10	20	15	75		196	190	180	170	160	150	140	130	10	10
7	SBR-20	11	22.5	17	75		215.6	209	198	187	176	165	154	143	11	11
8	SBR-20	12	25	18.5	75		235.2	228	216	204	192	180	168	156	12	12
9	SBR-20	13	25	18.5	75		254.8	247	234	221	208	195	182	169	13	13
10	SBR-20	14	30	22	75		274.4	266	252	238	224	210	196	182	14	14
11	SBR-20	15	30	22	75		294	285	270	255	240	225	210	195	15	15

