

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBR-25

Radial Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	ISI Mark	QM ³ /HR	0	21	24	27	28.5	30	31.5	34.5	37.5
							QLPM	0	350	400	450	475	500	525	575	625
							H/Stage	20.6	18	17	16	15	14	13	12	10
1	SBR-25	4	10	7.5	75	ISI	TOTAL HEAD IN METRE	82.4	72	68	64	60	56	52	48	40
2	SBR-25	5	12.5	9.3	75	ISI		103	90	85	80	75	70	65	60	50
3	SBR-25	6	15	11	75	ISI		123.6	108	102	96	90	84	78	72	60
4	SBR-25	7	20	15	75	ISI		144.2	126	119	112	105	98	91	84	70
5	SBR-25	8	20	15	75	ISI		164.8	144	136	128	120	112	104	96	80
6	SBR-25	9	25	18.5	75	ISI		185.4	162	153	144	135	126	117	108	90
7	SBR-25	10	25	18.5	75	ISI		206	180	170	160	150	140	130	120	100
8	SBR-25	11	27	20	75	ISI		226.6	198	187	176	165	154	143	132	110
9	SBR-25	12	30	22	75	ISI		247.2	216	204	192	180	168	156	144	120

