

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

### SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBR-40

Radial Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Out let Size mm	QM <sup>3</sup> /HR	0	18	27	33	39	43.5	48	49.5	54
						QLPM	0	300	450	550	650	725	800	825	900
						H/Stage	24.1	22	21	20	19	18	17	16	14
1	SBR-40	3	12.5	9.3	75	TOTAL HEAD IN METRE	72.6	66	63	60	57	54	51	48	42
2	SBR-40	4	15	11	75		96.4	88	84	80	76	72	68	64	56
3	SBR-40	5	20	15	75		121	110	105	100	95	90	85	80	70
4	SBR-40	6	25	18.5	75		145	132	126	120	114	108	102	96	84
5	SBR-40	7	27	20	75		169	154	147	140	133	126	119	112	98
6	SBR-40	8	30	22	75		193	176	168	160	152	144	136	128	112
7	SBR-40	9	35	26	75		217	198	189	180	171	162	153	144	126
8	SBR-40	10	40	30	75		241	220	210	200	190	180	170	160	140
9	SBR-40	11	45	33.5	75		265	242	231	220	209	198	187	176	154
10	SBR-40	12	50	37	75		289	264	252	240	228	216	204	192	168

