

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBS-50

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	QM ³ /HR	0	18	42	57	69	76.2	81.6	88.2
						QLPM	0	300	700	950	1150	1270	1360	1470
						H/Stage	19.6	18.3	16.7	15.5	14.0	12.5	11.1	10.1
1	SBS-50	2	10	7.5	100	TOTAL HEAD IN METRE	39	37	33	31	28	25	22	20
2	SBS-50	3	15	11	100		59	55	50	47	42	38	33	30
3	SBS-50	4	20	15	100		78	73	67	62	56	50	44	40
4	SBS-50	5	25	18.5	100		98	92	83	78	70	63	55	50
5	SBS-50	6	30	22	100		118	110	100	93	84	75	67	61
6	SBS-50	7	35	26	100		137	128	117	109	98	88	78	71
7	SBS-50	8	40	30	100		157	147	133	124	112	100	89	81
8	SBS-50	9	45	33.5	100		176	165	150	140	126	113	100	91
9	SBS-50	10	50	37	100		196	183	167	155	140	125	111	101
10	SBS-50	11	62	46.5	100		215	202	183	171	154	138	122	111
11	SBS-50	12	62	46.5	100		235	220	200	186	168	150	133	121

