

PRICE LIST / PERFORMANCE TABLE OF SUBMERSIBLE PUMP SET AT 415V, 3PHASE, 50 Hz, A.C. SUPPLY (2900 RPM)

SUITABLE FOR 200 mm (8") OR ABOVE DIA. BOREWELL

Model - SBS-60

Mixed Flow

Max. Out Side Dia. 193 mm

Sr. No.	Pump Type	Stage	HP	KW	Outlet Size mm	QM ³ /HR	0	12	19.8	39	69	87.6	97.8	103
						QLPM	0	200	330	650	1150	1460	1630	1715
						H/Stage	20.5	18.5	17.0	15.5	14.0	12.5	11.0	10.0
1	SBS-60	2	12.5	9.3	100	TOTAL HEAD IN METRE	41	37	34	31	28	25	22	20
2	SBS-60	3	20	15	100		62	56	51	47	42	38	33	30
3	SBS-60	4	25	18.5	100		82	74	68	62	56	50	44	40
4	SBS-60	5	30	22	100		103	93	85	78	70	63	55	50
5	SBS-60	6	35	26	100		123	111	102	93	84	75	66	60
6	SBS-60	7	45	33.5	100		144	130	119	109	98	88	77	70
7	SBS-60	8	50	37	100		164	148	136	124	112	100	88	80
8	SBS-60	10	62	46.5	100		205	185	170	155	140	125	110	100
9	SBS-60	11	72	53.5	100		226	204	187	171	154	138	121	110
10	SBS-60	12	72	53.5	100		246	222	204	186	168	150	132	120

